

Thunderbolt™ GM330 PTP Grandmaster Clock



Preliminary Datasheet v1.7




Overview

The Protempis Thunderbolt™ GM330 PTP Grandmaster Clock is designed for networks that require timing & phase synchronization, including applications in:

- Public & Private Wireless
- Data Centers
- Industrial networks & more

It provides continuous availability of UTC traceable time for phase synchronization, a critical need for LTE Advanced/5G networks and services.

Integration of Functions



The GM330 reduces the cost of deployment by integrating 3 functions:

- High accuracy GNSS timing with dual frequency & holdover
- Supports a broad range of PTP profiles and a high number of clients
- Integrated switch with optical or copper port options

Versatile Design

The GM330 can be used in either indoor or outdoor deployments that require an extended operating temperature range. It includes versatile I/O, Power-Over-Ethernet+ PD (option, coming soon) and a compact form factor to address a variety of time & sync use cases.

PTP Profiles

- IEEE-1588 v2.1
- ITU-T G.8265.1
- ITU-T G.8275.1
- ITU-T G.8275.2 PRTC-B, Telecom-2019
- IEEE 802.1AS
- Enterprise Profile
- Power (C37.238 2011)
- Broadcast (SMPTE ST-2059-2)

Applications

Small Cells

In addition to its rugged design, the GM330 addresses the tight timing requirements of typical small cell private wireless services. As more radios and small cells are deployed to ensure coverage, the GM330 offers a scalable solution with its client count that seamlessly addresses the growing network's time and sync needs.

4G LTE-A & 5G Services

The GM330 is a cost-effective solution for any network that requires stringent phase synchronization of 4G LTE-A/5G services. With its high reliability and purpose-built design, it easily deploys at the edge and/or network aggregation layer.

Private 5G & Industrial Data Networks

Third-party providers and municipalities are building their own private 5G networks instead of relying on WI-FI to achieve superior range and coverage. The GM330, with proven time and sync technologies, enables these organizations to meet key connectivity requirements, while its integration of functions reduces implementation cost.

Integration of Multiple Functions

- World Class GNSS Time & PTP Sync Technology
- Ethernet switch & ports
- NTP & PTP (on the same port)

GNSS Precision Timing

- Dual Frequency (L1 & L5)
- Multi-Constellation (GPS, GLONASS, Beidou, Galileo, NavIC, QZSS)
- 5ns (1-sigma) time stability
- Holdover: $\pm 1.5\mu s$ over 24 hours
- Anti-Jamming & Anti-Spoofing

PTP & Synchronization

- Widely used PTP Profiles
- PTP Client Count: 128 to 4000+ (dependent on profile & transaction rate)
- Usable as a PTP GM or Boundary Clock

Connectivity

- Inputs: GNSS, 1588-PTP, PPS, SyncE
- Outputs: 1588-PTP, NTP, SyncE, PPS, ToD, 10MHz
- Ethernet Ports:
 - 4x 1G/10G SFP+
 - 2x 10/100/1000 BASE-T RJ45
 - VLAN support
 - IPv4 & IPv6
- Supports SyncE over Optical Fiber & Copper

Other Key Features

- Operating Temperature: $-40^{\circ}C$ to $+70^{\circ}C$
- Hardware Time Stamping
- Supports POE+ PD (option, coming soon)
- Secure Boot
- Management: Serial port (1xRJ45), WebUI, CLI
- 19" Half-Rack (1U)

Applications

- Small Cell
- LTE Advanced/5G Synchronization
- Private 5G & Industrial Data Networks
- ORAN 5G
- Enterprise
- Oil & Gas and Enterprise
- Power & Utility
- Broadcast
- Financial



Disclaimer

Protempis does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others. Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or trade names, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.

Thunderbolt™ GM330 PTP Grandmaster Clock



General Specifications

Inputs: GNSS, PPS, CLK
Outputs: FREQ, PPS, SyncE, ToD
In/Out: NTP, PTP, SyncE
Square Wave CLK (10MHz)

Management Port:

1x Console Serial Port Up to 230K Bits/s RJ45

Ethernet Ports:

4x 1G/10G Copper/Optical SFP+
2x 10/100/1000BASE-T RJ45 (POE+ available on ETH0)

GNSS Antenna SMA (Female)
PPS_IN, PPS_OUT, CLK, FREQ, ToD SMA (Female)

Protocols:

IEEE-1588 (PTP), NTPv4, SyncE, IPv4, IPv6, TELNET, SFTP,
SSH, RADIUS, TACACS+, SNMP, DAYTIME, TIME

Monitoring & Management Interfaces:

CLI, Web UI (HTTPS), SNMPv2/v3, NETCONF, RESTCONF

Performance

Time of day stability 5ns (1-sigma) reference GNSS
Timestamp stability <10 ns
Frequency stability 1.16×10^{-12} (one-day avg)

Time Stability

Tracking to GNSS, dual frequency (L1 + L5)..... <5ns (locked)
Holdover..... < $\pm 1.5 \mu\text{s}/24\text{hrs}$ (7 days locked)
Power consumption 25W (max)

Physical Characteristics

Dimensions in cm (L x W x H) 20.8 x 20 x 4.4
(19" half-rack x 1U)

Power

DC Power, dual feed -36VDC to -72VDC
POE+ PD (option, coming soon)..... 25W (max)
Current consumption 500mA (max)

Regulatory & Standards

Operating Conditions

Temperature -40°C to +70°C
Humidity..... 5%-95% RH non-condensing (+60°C)
Storage Temperature -55°C to +105°C

Safety & Health

UL EN 62368-1, CE, CISPR32 class A, GR-63; Level 3
ETSI (EN55032/EN55024) EN 300019, Class T3.2
Electrical EMC, ESD Immunity & susceptibility
FCC Part 15 Class B / ICES 003 Class-B
Korea KN32 / KN35 Class A
EN 301 489-1, EN 301 489-19 EN 303 413

PTP Profiles: See page 1

Synchronization

ITU-T G.8265.x, G.8275.x (PRTC/T-GM)
IEEE PTP (IEEE 1588v2.1)
IETF NTPv4 (RFC5905)

Product Compliant with the following directive:

2014/53/EU (RED Directive)
2011/65/EU (RoHS2 Directive)
2012/19/EU (WEEE Directive)

Please visit www.protempis.com for the latest documentation and tools, part numbers and ordering information.



Disclaimer

Protempis does not assume any liability arising out of the application or use of any product described or shown herein nor does it convey any license under its patents, copyrights, or any rights of others. Licenses or any other rights such as, but not limited to, patents, utility models, trademarks or trade names, are neither granted nor conveyed by this document, nor does this document constitute any obligation of the disclosing party to grant or convey such rights to the receiving party.